



Hangcha Europe GmbH

Mariechen-Graulich-Straße 12a,
65439 Flörsheim am Main,
Germany

Administration
Tel: 0049-61453769188
E-mail: admin@hangchaeurope.com

Sales Management
Thomas Dittrich
Mob: 0049-16096548808
E-mail: thomas.dittrich@hangchaeurope.com

Technical Support
Thomas Pannke
Mob: 0049-01759284213
E-mail: thomas.pannke@hangchaeurope.com

www.hangchaeurope.com



Folgen Sie uns auf
Instagram



Folgen Sie uns auf
Facebook



Folgen Sie uns auf
YouTube



"Hangcha Forklift"
App herunterladen



ISO14001:2015



ISO9001:2015



HANGCHA trucks conform
to the European Safety
Requirements.

HANGCHA Group Co., LTD behält sich das Recht vor, Änderungen bezgl. Farbe, Spezifikationen, Ausstattung und sonstige Details, dierer Broschüre ohne Vorankündigung vorzunehmen. Fahrzeugfarben können von den Farben in dieser Brochure abweichen.



X SERIES

DIESEL TELEHANDLER

With capacity of 4,000kg

X SERIES

DIESEL TELEHANDLER

HANGCHA Family-Design exterior, ergonomic cab, intuitive HMI system and premium driving comfort experience.



HIGH-PERFORMANCE MACHINES IN ANY SITUATION

THREE STEERING MODES:



4WD

FOUR-WHEEL DRIVE



With efficient operation performance, the maximum speed is 35 km/h, the maximum climbing ability is 40%, and the lifting height is industry-leading in the same category.

 **35 km/h** |  **40%**
Drive speed (no load) Gradeability



The machine is equipped with quick change device, which can realize the quick replacement of different attachments. This enables various operations including fork loading, shovel loading, clamping, aerial work, etc.

Key components are sourced from internationally renowned brands. Structural components are rigorously verified through both CAE analysis and actual measurements, ensuring high reliability.

COMFORT

01

Adjustable suspension seat can provide more ergonomic.

02

Full-proportional joystick, smooth and coordinated movements, smooth and steady on start and stop, boom luffing and telescoping support multi-movements.

03

7 inch display, real-time machine status monitoring, integrated intelligent fault diagnosis system.

04

The cab can be equipped with air conditioning, radio, and USB charging port as option.

MAINTENANCE

- A maintenance arm is provided on the vehicle to prevent the boom from accidentally falling during maintenance.
- Wide-angle tilting cover ensures easy maintenance access.

SAFETY

- The lighting system is excellent. Besides the High and low beam headlights, LED high-brightness working lights are also provided in the cab front and rear and the boom respectively, ensuring operation in night scenarios.
- Equipped with overload monitoring system, it can conduct real-time dynamic monitoring to prevent overturning and overloading, and timely restrict actions to avoid accidents.



Technical data

		HANGCHA GROUP CO.,LTD.	
Lifting capacity	Manufacturer	HANGCHA GROUP CO.,LTD.	
	Model	T40-180XH16D	T40-180XW70D
	Max.lift capacity	kg	4000
	Lift capacity at maximum height	kg	2500
	Lift capacity at maximum reach	kg	850
	Max. lifting height	mm	17700
	Max. forward reach	mm	13020
Dimensions and Weight	Load centre distance	mm	500
	A Front overhang	mm	1990
	B Wheelbase	mm	3450
	C Tread	mm	2050
	D Overall length	mm	6630
	E Fork dimension	mm	1200*122*50
	F Overall height	mm	2500
	G Overall width	mm	2450
	H Cabin width	mm	940
	J Min. Ground clearance	mm	400
	K1 Tilt-up angle	°	12
	K2 Tilt-down angle	°	114
	L Min. turning radius	mm	4100
	weight	kg	13700
Wheels	Tyre type	Vacuum tire	Vacuum tire
	Tyre size	400/75-28	400/75-28
	Drive wheel x Steering wheel	4x4	4x4
Performance parameters	Frame leveling Angle	°	10
	Boom lower/raise angle	°	-4/72
	Boom raising time (no load)	s	17
	Boom lowering time (no load)	s	15
	Extension time (no load)	s	20
	Retract time (no load)	s	16
	Fork backward time (no load)	s	6
	Fork forward time (no load)	s	6
	Max. travel speed (no load)	km/h	35
	Max. Drawbar pull	N	80000
	Gradeability	%	40
Power	Engine model	Cummins F3.8	Cummins QSF3.8t3TC115
	Engine Power	kW/r/min	90/2200
	Engine Torque	N/r/min	500/1500
	System voltage	V	24
	Battery	V/CCA	2x12V/600CCA
	Fuel tank capacity	L	160
	Hydraulic tank capacity	L	190

Features

Truck	Standard	Options
Air conditioner		○
Quick exchange fork carriage	●	
Adjustable suspension seat	●	
Flame retardant leather seats	●	
Traction device	●	
Load moment limiter Overload monitoring devise	●	
Left operable window	●	
Horn	●	
Key switch	●	
Wide angle L/R rearview mirrors	●	
Panoramic reversing mirror	●	
Front wiper with water spray function	●	
Rear window wiper	●	
High and low beam headlights	●	
Front and rear work lights	●	
Working light	●	
Reverse light	●	
Windshield protective frame		○
Fire Extinguisher		○
Foam filled tire		○
Quick change heavy Duty Multi-Purpose Bucket		○
Quick change crane arm		○
Forklift arm		○
400/75-28 Penumatic tire	●	
Fordward 4 gears/Reverse 3 gears	●	
Dual axis stabilizer	●	
Horizontal leveling system of the chassis	●	
Action buzzer	●	
Fuel filter	●	
Load backrest	●	
Quick change soft bag clip		○
Boom angle indicator		○
Steering		
Three steering modes	●	
Adjustable steering column	●	
Hydraulic		
Hydraulic quick coupler	●	
Tilt cylinder self-locking valve	●	
Self locking valve for telescopic oil cylinder	●	
Lifting cylinder self-locking valve	●	
Lifting cylinder maintenance arm	●	
Hydraulic Oil Filter	●	
Hydraulic oil air filter	●	
Hydraulic oil dipstick	●	
High efficient and adjustable flow hydraulic pump	●	
Power		
2WD and 4WD switch function	●	
Transmission		
Wet brake	●	
Limited slip differential	●	
Hydraulic power steering	●	
Control		
Dual axis proportional control handle	●	
Emergency stop switch	●	
Parking brake	●	
Electronics		
Fault self diagnosis function	●	
7-inch color multifunctional display screen	●	
Warning lamp for not fastening the seat belt	●	
Heater	●	
Reading light	●	
Radio	●	
Safety		
Warning light	●	
Reverse alarm	●	
Reverse camera		○
Reverse radar		○

