



Hangcha Europe GmbH

Mariechen-Graulich-Straße 12a,
65439 Flörsheim am Main,
Germany

Administration
Tel: 0049-61453769188
E-mail: admin@hangchaeurope.com

Sales Management
Thomas Dittrich
Mob: 0049-16096548808
E-mail: thomas.dittrich@hangchaeurope.com

Technical Support
Thomas Pannke
Mob: 0049-01759284213
E-mail: thomas.pannke@hangchaeurope.com

www.hangchaeurope.com



Folgen Sie uns auf
Instagram



Folgen Sie uns auf
Facebook



Folgen Sie uns auf
YouTube



"Hangcha Forklift"
App herunterladen



ISO14001:2015



ISO9001:2015



HANGCHA trucks conform
to the European Safety
Requirements.

HANGCHA Group Co., LTD behält sich das Recht vor, Änderungen bezgl. Farbe, Spezifikationen, Ausstattung und sonstige Details, dierer Bröschüre ohne Vorankündigung vorzunehmen. Fahrzeugfarben können von den Farben in dieser Brochure abweichen.

2025 VERSION 1 / COPYRIGHT 2025/04



X Series Electric Forklift Truck

with capacities of 6,000 to 10,000kg

The World of Hangcha






Exterior

- / A new exterior design method is used to form a stylish and elegant exterior with streamlined curved surfaces and smooth ethereal lines.
- / The vehicle is compact, simple and sturdy in appearance.
- / A fully enclosed console space.

Stability

- / Small-diameter solid tires, front and rear battery sets and other technologies are used to enable excellent stability of the vehicle.



Comfort

- / The inclination angle of the ergonomically designed hand wheel is adjustable and the seat can be adjusted 150mm forwards and backwards, so that the operator can choose the best driving position.
- / Two independent hydraulic systems for steering braking and hydraulic lifting respectively are used to ensure the steering braking performance and the combined operations to be carried out.
- / The dashboard, tilt cylinder and flat bottom panel are designed to be fully enclosed to enable more comfortable and safer operations.
- / The multifunctional color-screen instruments have clear human-computer interfaces displaying clear readings.
- / Personalized design: overlarge storage bin, USB port, etc.

Safety

- / The optimized design of the wide-view mast, wide-view overhead guard and low dashboard enables a broader view of the operator and higher safety.
- / The LED headlights and combination lights enable the operator to have a good view in various circumstances.
- / The all-round vision rearview mirror provides a broader rear view and higher driving safety.
- / The intelligent sensing enables buffered descending. When the fork is 100 - 60mm away from the ground, the descending will automatically slow down, so that the goods and pallet will not hit the ground and the goods and ground can be protected effectively.
- / The electronic and hydraulic overload protection devices comply with safety regulations.
- / An optional OPS safety system is provided.

Maintainability

- / The fully open front and rear battery lids easily facilitate battery maintenance.
- / The innovative two-door structure with one door, respectively, on the left and right sides of the forklift easily facilitates the maintenance of the motor, oil pump and electric control of the forklift and enables good resistance to dust and water.
- / The foot panel can be dismounted without a tool and facilitates the overhaul and maintenance of the driving motor and various systems.
- / The brake fluid can be added after the shroud cap and the oil tank cap are opened.
- / An optional laterally-dismounted battery is provided to enable quick replacement of the battery.





Advancement

- / The high-frequency MOSFET integrated controller ensures smooth and accurate driving and lifting control, and has excellent speed regulation performance, good performance of electronic control matching the motor, functions of regenerative braking, reverse braking and anti-sliding on ramps, etc. and high safety and reliability.
- / The branded multifunctional color-screen instruments have the functions of battery display, timer and fault diagnosis and can accurately display information under harsh environments.
- / The branded AC controller enables the forklift's driving, steering, lifting, tilting and other actions to be controlled by a computer.
- / Regenerative braking (when stopping, slowing down, reversing or driving down a ramp, etc., being energy-saving and efficient, the forklift can have its drive motor working as a power generator to charge the battery through the controller.)
- / The main electrical components such as the motor controller, contactor, power plug and emergency cut-off switch are all branded high-quality products.

High speed, high efficiency

- / With several speed gears, the vehicle is adapted to different operating environments.
- / With a high-power driving motor and a high speed ratio gearbox, an 8t vehicle, for example, can have its maximum full-load driving speed increased to 14.5km/h and maximum full-load upslope degree increased by up to 14%.
- / A high-power oil pump motor and a large-displacement silent pump are used to significantly improve the lifting speed. An 8t vehicle, for example, can have its maximum full-load lifting speed increased to 300mm/s.
- / A new compact design concept is adopted to reduce the width of the vehicle.
- / Light weight and low driving power consumption. The brake kinetic energy regeneration system effectively saves on electric power and improves the use time after a single charge.



Options

- / Seamless solid tire
- / Triple and quadruple multiway valves
- / Alarm light
- / Rear LED operation light
- / Blue light
- / Rear reversing armrest horn button
- / Large-capacity battery
- / PVC ceiling
- / Battery charger
- / OPS
- / Fingertip system
- / Video monitoring system
- / Fully-suspended seat
- / Fully enclosed cab
- / Left and right rear view mirrors
- / Free duplex mast
- / Free triplex mast
- / Forks of other lengths
- / Heightened or widened fork carriage
- / Other attachments
- / Double front wheels
- / Battery removed sideways
- / Large tool box, folder
- / Fork positioner

Standard specification

- / AC electric control motor
- / Emergency power off switch
- / Multifunctional color-screen instruments
- / Super-elastic solid tire
- / Two-way multi-way valve
- / Rubber pedal pads of all sizes
- / 3 m duplex wide-field-of-view mast
- / Vehicle LED lights
- / Panoramic rear view mirror
- / Fully hydraulic power steering
- / Angle-adjustable steering column
- / Horn, reversing buzzer
- / Intelligent descending buffering device
- / Traction pin
- / Silent gear pump

Battery Specification

Battery	Capacity (Ah/5h)	6t	7t	8t	8t Long wheelbase	9t	10t
Lead-acid	720	●					
	810	○	●				
	945	○	○	●	●		
	1035		○	○			
	1104				○	●	
	1260				○	○	●
	1380				○	○	○
CATL Lithium	604	●	●	●			
	684	○	○	○	●	●	●
	906	○	○	○	○	○	○
Hangcha Lithium	560	○	○	○			
	608	○	○	○	○	○	○
	840	○	○	○	○	○	○
	912				○	○	○

Note: ● Battery Std; ○ Battery Opt;

6.0-8.0t tyre options

Model	Solid tyres and dimensions spec.						Pneumatic tyres and dimensions spec.				
	Tyre size, front		Tyre size, rear		Tread, front	Overall width	Tyre size, front		Tyre size, rear	Tread, front	Overall width
CPD60	355/65-15(single tyre)	●	250-15	●	1574	1870	355/65-15-24PR(single tyre)	250-15-18PR	○	1574	1940
	8.25-15(dual tyre)	○	250-15	●	1489	1970	8.25-15-16PR(dual tyre)	250-15-18PR	○	1489	2000
CPD70	355/65-15(single tyre)	●	250-15	●	1574	1870	355/65-15-24PR(single tyre)	250-15-18PR	○	1574	1940
	8.25-15(dual tyre)	○	250-15	●	1489	1970	8.25-15-16PR(dual tyre)	250-15-18PR	○	1489	2000
CPD80	355/50-20(single tyre)	●	250-15	●	1623	1945	-	-	○	-	-
	8.25-15(dual tyre)	○	250-15	●	1489	1970	8.25-15-16PR(dual tyre)	250-15-18PR	○	1489	2000

The single solid tyre is suitable for gap work, with a maximum working distance of 2km.

Note: ● Std; ○ Opt;

FORKLIFT TRUCK FOR WORK IN CONTAINER



X series lithium battery forklift truck for work in container



			CPD60-XC4-IX	CPD70-XC4-IX	CPD80-XC4-IX	CPD80-XLC4-IX	CPD90-XC4-IX	CPD100-XC4-IX
4.1	Tilt of mast/fork carriage forward/backward	$\alpha/\beta(^{\circ})$	5/10	5/10	5/10	5/8	5/8	5/8
4.2	Height, mast lowered	h1(mm)	2185	2185	2185	2200	2200	2200
4.3	Free lift	h2(mm)	1048	1048	920	680	680	680
4.4	Lift	h3(mm)	2500	2500	2200	2000	2000	2000
4.5	Height, mast extended	h4(mm)	3637	3637	3465	3520	3520	3520
4.7	Height of overhead guard	h6(mm)	2230	2230	2230	2230	2230	2230

Note: Std. Full free duplex mast.
Not CE model


X Series 6.0-10t Electric Forklift Specification

Distinguishing mark	1.1	Manufacturer		HANGCHA GROUP CO.,LTD.											
	1.2	Manufacturer's type designation		CPD60-XC5* CPD60-XD3*	CPD70-XC5* CPD70-XD3*	CPD80-XC5* CPD80-XD3*	CPD80-XLC5* CPD80-XLD3*	CPD90-XC5* CPD90-XD3*	CPD100-XC5* CPD100-XD3*	CPD60-XC5-I* CPD60-XD3-I*	CPD70-XC5-I* CPD70-XD3-I*	CPD80-XC5-I* CPD80-XD3-I*	CPD80-XLC5-I* CPD80-XLD3-I*	CPD90-XC5-I* CPD90-XD3-I*	CPD100-XC5-I* CPD100-XD3-I*
	1.3	Drive: electric (battery or mains), diesel, petrol, fuel gas		Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric
	1.4	Operator type: hand, pedestrian, standing, seated, order-picker		Seated	Seated	Seated	Seated	Seated	Seated	Seated	Seated	Seated	Seated	Seated	Seated
	1.5	Rated capacity/rated load	Q (kg)	6000	7000	8000	8000	9000	10000	6000	7000	8000	8000	9000	10000
	1.6	Load centre distance	c (mm)	600	600	600	900	600	600	600	600	600	900	600	600
	1.8	Load distance, centre of drive axle to fork	x (mm)	598.5	603.5	623.5	640	640	640	598.5	603.5	623.5	640	640	640
	1.9	Wheelbase	y (mm)	2030	2030	2030	2500	2500	2500	2030	2030	2030	2500	2500	2500
Weight	2.1	Service Weight	kg	9600	10280	12180	13530	12960	13780	9030	9400	11230	12480	11750	13180
	2.2	Axle loading, laden front/rear	kg	13600/2000	15180/2100	17710/2470	19130/2400	19560/2400	21230/2550	13190/1840	14550/1850	17270/1970	18080/2400	18620/2130	20630/2550
	2.3	Axle loading, unladen front/rear	kg	4000/5600	3950/6300	4890/7290	6030/7500	5910/7050	6080/7700	3650/5380	3400/6000	4450/6780	4980/7500	4980/6770	5480/7700
Tyres, chassis	3.1	Tyres: solid rubber, superelastic, pneumatic, polyurethane		SE	SE	SE	SE	SE	SE	SE	SE	SE	SE	SE	SE
	3.2	Tyre size, front		355/65-15	355/65-15	355/50-20	8.25-15	8.25-15	300-15	355/65-15	355/65-15	355/50-20	8.25-15	8.25-15	300-15
	3.3	Tyre size, rear		250-15	250-15	250-15	250-15	250-15	250-15	250-15	250-15	250-15	250-15	250-15	250-15
	3.5	Wheels, number front / rear (x = driven wheels)		2x/2	2x/2	2x/2	4x/2	4x/2	4x/2	2x/2	2x/2	2x/2	4x/2	4x/2	4x/2
	3.6	Tread, front	b1o (mm)	1574	1574	1623	1489	1489	1493	1574	1574	1623	1489	1489	1493
	3.7	Tread, rear	b11 (mm)	1536.5	1536.5	1536.5	1536.5	1536.5	1536.5	1536.5	1536.5	1536.5	1536.5	1536.5	1536.5
Dimensions	4.1	Tilt of mast/fork carriage forward/backward	α/β(°)	5/10	5/10	5/10	5/10	5/10	5/10	5/10	5/10	5/10	5/10	5/10	5/10
	4.2	Height, mast lowered	h1 (mm)	2500	2500	2650	2700	2700	2700	2500	2500	2650	2700	2700	2700
	4.3	Free lift	h2 (mm)	160	160	175	200	200	200	160	160	175	200	200	200
	4.4	Lift	h3 (mm)	3000	3000	3000	3000	3000	3000	3000	3000	3000	3000	3000	3000
	4.5	Height, mast extended	h4 (mm)	4407	4407	4407	4530	4530	4530	4407	4407	4407	4530	4530	4530
	4.7	Height of overhead guard	h6 (mm)	2565	2565	2565	2565	2565	2565	2565	2565	2565	2565	2565	2565
	4.8	Seat height/stand height	h7 (mm)	1430	1430	1430	1430	1430	1430	1430	1430	1430	1430	1430	1430
	4.12	Coupling height	h1o (mm)	423	423	423	423	423	423	423	423	423	423	423	423
	4.19	Overall length	l1 (mm)	4395	4400	4420	5505	4905	4905	4395	4400	4420	5505	4905	4905
	4.20	Length to face of forks	l2 (mm)	3195	3200	3220	3705	3705	3705	3195	3200	3220	3705	3705	3705
	4.21	Overall width	b1 (mm)	1870	1870	1945	1970	1970	2066	1870	1870	1945	1970	1970	2066
	4.22	Fork dimensions	s/e/l (mm)	60/150/1200	65/150/1200	65/200/1200	80/200/1800	80/170/1200	80/170/1200	60/150/1200	65/150/1200	65/200/1200	80/200/1800	80/170/1200	80/170/1200
	4.23	Fork carriage DIN 15 173 --- ISO 2328, class/type A,B		ISO 2328 4A	ISO 2328 4A	ISO 2328 4A	ISO 2328 4A	ISO 2328 5A	ISO 2328 5A	ISO 2328 4A	ISO 2328 4A	ISO 2328 4A	ISO 2328 4A	ISO 2328 5A	ISO 2328 5A
	4.24	Fork-carriage width	b3 (mm)	1700	1700	1700	1800	1800	1800	1700	1700	1700	1800	1800	1800
	4.25	Distance between fork-arms	b5 (mm)	300-1700	300-1700	400-1700	400-1800	340-1800	340-1800	300-1700	300-1700	400-1700	400-1800	340-1800	340-1800
	4.31	Ground clearance, laden, below mast	m1 (mm)	183	183	183	183	183	183	183	183	183	183	183	183
	4.32	Ground clearance, centre of wheelbase	m2 (mm)	200	200	200	200	200	200	200	200	200	200	200	200
	4.34.1	Aisle width for pallets 1000 x 1220 crossways	As1 (mm)	4848.5	4853.5	4873.5	5190	5180	5190	4848.5	4853.5	4873.5	5190	5180	5190
	4.34.2	Aisle width for pallets 1200 x 1000 lengthways	As1 (mm)	5048.5	5053.5	5073.5	5390	5380	5390	5048.5	5053.5	5073.5	5390	5380	5390
	4.35	Turning radius	Wα (mm)	3050	3050	3050	3350	3350	3350	3050	3050	3050	3350	3350	3350
Performance data	5.1	Travel speed, laden/unladen	km/h	15/15.5	15/15.5	14.5/15.5	14.5/15.5	13.5/15.5	13.5/15.5	15/15.5	15/15.5	14.5/15.5	14.5/15.5	13.5/15.5	13.5/15.5
	5.2	Lift speed, laden/unladen	m/s	0.34/0.39	0.32/0.39	0.3/0.39	0.3/0.44	0.28/0.4	0.25/0.4	0.34/0.39	0.32/0.39	0.3/0.39	0.3/0.44	0.28/0.4	0.25/0.4
	5.3	Lowering speed, laden/unladen	m/s	0.45/0.4	0.5/0.34	0.545/0.345	0.545/0.345	0.545/0.345	0.545/0.345	0.45/0.4	0.5/0.34	0.545/0.345	0.545/0.345	0.545/0.345	0.545/0.345
	5.6	Max. Drawbar pull	N	36000	36000	36000	36000	36000	36000	36000	36000	36000	36000	36000	36000
	5.8	Max. gradeability, laden	%	16	15	14	13	12	12	16	15	14	13	12	12
	5.10	Service brake		Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
		Parking brake		Mechanical	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical
Electric-engine	6.1	Drive motor rating S2 60 min	kW	35	35	35	35	35	35	35	35	35	35	35	35
	6.2	Lift motor rating at S3 15%	kW	40	40	40	52	52	52	40	40	40	52	52	52
	6.3	Battery acc. to DIN 43531/35/36 A,B,C, no		no	no	no	no	no	no	no	no	no	no	no	no
	6.4	Battery voltage, nominal capacity K5	V/Ah	96/720	96/810	96/945	96/945	96/1104	96/1260	96/604	96/604	96/604	96/684	96/684	96/684
	6.5	Battery weight	kg	2310	2510	2820	2880	3430	3880	580	580	580	640	640	640
		Battery dimensions	l/b/h(mm)	1420×610×570	1420×610×570	1420×610×570	1420×825×570	1420×825×570	1420×825×570	1420×610×580	1420×610×580	1420×610×580	1500×610×625	1500×610×625	1500×610×625
		Max. battery weight	kg	2970	3500	3500	4720	4720	4720	780	780	780	780	780	780
		Min. battery weight	kg	2310	2510	2820	2880	3430	3880	580	580	580	640	640	640
	8.1	Type of drive unit		MOSFET/AC	MOSFET/AC	MOSFET/AC	MOSFET/AC	MOSFET/AC	MOSFET/AC	MOSFET/AC	MOSFET/AC	MOSFET/AC	MOSFET/AC	MOSFET/AC	MOSFET/AC
	9.1	Manufacturer/Type		CURTIS INMOTION	CURTIS INMOTION	CURTIS INMOTION	CURTIS INMOTION	CURTIS INMOTION	CURTIS INMOTION	CURTIS INMOTION	CURTIS INMOTION	CURTIS INMOTION	CURTIS INMOTION	CURTIS INMOTION	CURTIS INMOTION
Addition data	10.1	Operating pressure for attachments	bar	190	190	190	190	190	190	190	190	190	190	190	190
	10.2	Oil volume for attachments	l/min	120	120	120	120	180	180	120	120	120	120	180	180
	10.3	Hydraulic Tank - capacity (drain & refill)	liter	98	98	98	153	153	153	98	98	98	153	153	153
	10.8	Towing coupling, type DIN 15170		Φ40 Pin	Φ40 Pin	Φ40 Pin	Φ40 Pin	Φ40 Pin	Φ40 Pin	Φ40 Pin	Φ40 Pin	Φ40 Pin	Φ40 Pin	Φ40 Pin	Φ40 Pin

Note: * CE model



RATED CAPACITY AND LOAD DIAGRAM



Mast Specification

Type	Max. fork height	Lowered	Overall height		Free lift		Tilt range		Capacity	
			With backrest	Without backrest	With backrest	Without backrest	F	R	load capacity at 600mm	
			mm	mm	mm	mm	(°)	(°)	6t kg	7t kg
STD .Duplex	mm	mm	mm	mm	mm	mm				
	2500	2250	3907	3495/3667	160	160	5	10	6000	7000
	2700	2350	4107	3695/3867	160	160	5	10	6000	7000
	3000	2500	4407	3995/4167	160	160	5	10	6000	7000
	3300	2650	4707	4295/4467	160	160	5	10	6000	7000
	3600	2800	5007	4595/4767	160	160	5	10	6000	7000
	4000	3000	5407	4995/5167	160	160	5	10	6000	7000
	4300	3200	5707	5300/5467	160	160	5	8	6000	7000
	4500	3300	5907	5500/5667	160	160	5	8	6000	7000
	4800	3450	6207	5800/5967	160	160	5	8	5800	6700
	5000	3550	6407	6000/6167	160	160	5	8	5700	6500
	5500	3850	6907	6550/6667	160	160	5	8	5400	6200
	6000	4100	7407	7050/7167	160	160	5	8	5000	5900
	2500	2185	3637	3455/3615	1048	1230/1070	5	10	6000	7000
	2700	2300	3837	3655/3815	1163	1345/1185	5	10	6000	7000
Full Free Lift	3000	2450	4137	3955/4115	1313	1495/1335	5	10	6000	7000
	3300	2600	4437	4255/4415	1463	1645/1485	5	10	6000	7000
	3600	2750	4737	4555/4715	1613	1795/1635	5	10	5800	6800
	4000	2950	5137	4955/5115	1813	1995/1835	5	10	5800	6800
	4500	2725	5907	5735	1328	1500	5	8	5700	6700
Triplex	4800	2825	6207	6035	1428	1600	5	8	5600	6600
	5000	2875	6407	6213	1478	1672	5	8	5500	6400
	5500	3075	6907	6785	1678	1800	5	8	5300	6200
	6000	3225	7407	7235	1828	2000	5	8	5200	5800

Mast Specification

Type	Max. fork height	Lowered	Overall height		Free lift		Tilt range		Capacity	
			With backrest	Without backrest	With backrest	Without backrest	F	R	load capacity at 600mm	
			mm	mm	mm	mm	(°)	(°)	9t kg	10t kg
STD .Duplex	mm	mm	mm	mm	mm	mm				
	2500	2450	4030	3900	200	200	5	8	9000	10000
	2700	2550	4230	4100	200	200	5	8	9000	10000
	3000	2700	4530	4400	200	200	5	10	9000	10000
	3300	2850	4830	4700	200	200	5	10	9000	10000
	3600	3000	5130	5000	200	200	5	10	9000	10000
	4000	3200	5530	5400	200	200	5	10	9000	10000
	4300	3400	5830	5700	200	200	5	8	9000	10000
	4500	3500	6030	5900	200	200	5	8	8500	9500
	4800	3650	6330	6200	200	200	5	8	8400	9400
	5000	3750	6530	6400	200	200	5	8	8300	9300
	5500	4050	7030	6900	200	200	5	8	8100	9100
	6000	4300	7530	7400	200	200	5	8	7700	8700
	3000	2700	4520	4390	1180	1310	5	10	9000	10000
	3300	2850	4820	4690	1330	1460	5	10	9000	10000
Full Free Lift	3600	3000	5120	4990	1480	1610	5	10	8900	9900
	4000	3200	5520	5390	1680	1810	5	10	8700	9700
	4500	2850	6055	6055	1305	1305	5	8	8600	9600
Triplex	4800	2950	6355	6355	1405	1405	5	8	8200	9200
	5000	3050	6555	6555	1505	1505	5	8	8000	9000
	5500	3200	7055	7055	1655	1655	5	8	7900	8900
	6000	3350	7555	7555	1805	1805	5	8	7500	8500

Mast Specification

Type	Max. fork height	Lowered	Overall height		Free lift		Tilt range		Capacity	
			With backrest	Without backrest	With backrest	Without backrest	F	R	load capacity at 600mm	
			mm	mm	mm	mm	(°)	(°)	8t kg	
STD .Duplex	2500	2400	3907	3817	175	175	5	10	8000	
	2700	2500	4107	4017	175	175	5	10	8000	
	3000	2650	4407	4317	175	175	5	10	8000	
	3300	2800	4707	4617	175	175	5	10	8000	
	3600	3000	5007	4917	175	175	5	10	8000	
	4000	3200	5407	5317	175	175	5	10	8000	
	4300	3300	5707	5617	175	175	5	8	8000	
	4500	3450	5907	5817	175	175	5	8	8000	
	4800	3550	6207	6117	175	175	5	8	7700	
	5000	3850	6407	6317	175	175	5	8	7500	
	5500	4100	6907	6817	175	175	5	8	7200	
	6000	4350	7407	7317	175	175	5	8	6900	
	3000	2600	4265	4265	1335	1335	5	10	8000	
	3300	2750	4565	4565	1485	1485	5	10	8000	
	3600	2900	4865	4865	1635	1635	5	10	7800	
Full Free Lift	4000	3100	5265	5265	1835	1835	5	10	7800	
	4500	2725	5907	5862	1328	1373	5	8	7600	
	4800	2825	6207	6162	1428	1473	5	8	7500	
Triplex	5000	2875	6407	6362	1478	1523	5	8	7400	
	5500	3075	6907	6862	1678	1723	5	8	7200	
	6000	3225	7407	7362	1828	1873	5	8	6800	

Note: With load backrest; 6-8t Height of standard load backrest is 1270 mm, 8L-10t Height of standard load backrest is 1393 mm.

Mast Specification

Type	Max. fork height	Lowered	Overall height		Free lift		Tilt range		Capacity	
			With backrest	Without backrest	With backrest	Without backrest	F	R	load capacity at 900mm	
			mm	mm	mm	mm	(°)	(°)	8t kg	
STD .Duplex	2500	2450	4030	3894	200	200	5	8	8000	
	2700	2550	4230	4094	200	200	5	8	8000	
	3000	2700	4530	4394	200	200	5	10	8000	
	3300	2850	4830	4694	200	200	5	10	8000	
	3600	3000	5130	4994	200	200	5	10	8000	
	4000	3200	5530	5394	200	200	5	10	8000	
	4300	3400	5830	5694	200	200	5	8	8000	
	4500	3500	6030	5894	200	200	5	8	7800	
	4800	3650	6330	6194	200	200	5	8	7600	
	5000	3750	6530	6394	200	200	5	8	7400	
	5500	4050	7030	6894	200	200	5	8	7200	
	6000	4300	7530	7394	200	200	5	8	6900	
	3000	2700	4520	4400	1180	1310	5	10	8000	
	3300	2850	4820	4700	1330	1460	5	10	8000	
	3600	3000	5120	5000	1480	1610	5	10	8000	
Full Free Lift	4000	3200	5520	5400	1680	1810	5	10	7800	
	4500	2850	6055	6055	1305	1305	5	8	7600	
	4800	2950	6355	6355	1405	1405	5	8	7500	
Triplex	5000	3050	6555	6555	1505	1505	5	8	7400	
	5500	3200	7055	7055	1655	1655	5	8	7200	
	6000	3350	7555	7555	1805	1805	5	8	6800	

Note: With load backrest; 6-8t Height of standard load backrest is 1270 mm, 8L-10t Height of standard load backrest is 1393 mm.

